

Hydrogen as an Energy Carrier: A Materials Perspective

Amarante Böttger – Materials Science and Engineering
Delft University of Technology

a.j.bottger@tudelft.nl



1

Hydrogen economy : History

- "Mystery Island" Jules Vernes 1874

The engineer says: *"je crois que l'eau sera un jour employée comme combustible, que l'hydrogène et l'oxygène, qui la constituent, utilisés isolément ou simultanément, fourniront une source de chaleur et de lumière inépuisables"*



- H - economy 1970 by J. Bocris




- High energy density : H_2 142 MJ kg^{-1} , liq. HC 47 MJ kg^{-1}
- Can be used to store and transport energy
- Abundant
- Secondary energy source - production



2

Hydrogen as an energy carrier

- Production
- Transport & Storage



400 km
Combustion: 24 kg petrol or 8 kg H_2
Fuel cell: 4 kg H_2

Hydrogen production

€ x3



Image by courtesy of David van Nunen

Electrolysis of H_2O






www.hysep.com/basic-info/index.html

from fossil fuel by
Steam Methane Reforming



90% of H_2

Hydrogen production from fossil fuel



Energy efficient by removing H_2 from reaction mixture

Membrane reactor



•Process Conditions

T: 550 – 950 K


P: 10 - 50 bar

•Stable alloy



- *delamination*
- *embrittlement*
- *segregation*

Metal membranes for gas separation


Microstructural changes	Surface poisoning
<ul style="list-style-type: none"> ○ Thermal expansion mismatch ○ β-hydride formation below T_c 	<ul style="list-style-type: none"> ○ H_2S, H_2O, CO, CO_2 ○ Surface segregation



vacuum gas environment



Optimise composition for stability



7

Pd : nano-structuring & embrittlement

Single H_2 loading – deloading cycle



Pd-compact morphology




Pd loose nano-sized structure

TU Delft


8

Optimise microstructure for stability

- Nano-structuring
 - Quasi-free expansion




Brush membrane concept




Loose nano-sized columnar structure : sputter conditions

- adhesive layer:



Improve adhesion


- Hydrogen loading and de-loading cycles
- Analysis of:
 - Phase transformation
 - Stress
 - Texture




Optimal film performance

Pd on PI : good adhesion – no delamination
high performance – solubility and kinetics

- Resulting optimal film characteristics:
 - Open nano-structure
 - Texture: ‘weak’ 111-texture 1,5 x random
 - Stress: ~ 100 MPa




Pd on PI film




Phase transformation and damage

Effect of hydrogen loading on dislocation density



Phase transformation and damage



Hydride formation ($T < 353$ K)

Heating up to 625 K + Hydride formation


TU Delft

13

Segregation

• Segregation in binary alloys

- H_2 , CO, CO_2 (H_2S , H_2O)
- Surface segregation



regular solution model - in vacuum

$$Q_{seg} = (\gamma_A \sigma_A - \gamma_B \sigma_B) + 2\omega Z_l (X_A^b - X_A^s) + 2\omega Z_v (X_A^b - \frac{1}{2})$$


surface

configurational

$$\omega = \epsilon_{AB} - \left(\frac{\epsilon_{BB} + \epsilon_{AA}}{2} \right)$$

TU Delft

Surface segregation



TU Delft


Image by courtesy of J.Postma -2020

Meng et al. Int.J. Hydr. Ener. 43 (2018) 2212s

15

Hydrogen as an energy carrier

- Production
- Transport & Storage




TU Delft


16

Hydrogen transport & storage

Capacity (**mass**, volume)
 Reversible – (P-C-T) **P, T moderate**
Kinetics (absorption/desorption)
Lifetime



TU Delft



17

Conclusion

- Materials design needed for
 - Efficient & low cost green hydrogen production
 - Existing infrastructure H-proof
 - Storage in solids (solubility, kinetics)

TU Delft

18

Thanks to

Vanya Uluc

Xiao Zheng

Daniel Enciso

Diana Nanu

Frans Tichelaar

Ruud Hendrikx

Meng Zhao

Shunli Shang

Neha Verma

Richard Huizenga



Katherine Encalada



A.J.Bottger@tudelft.nl 19